

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022  
Issue date: 2020-03-17 Revision date: 2025-08-21 Supersedes: 2020-03-19 Version: 3.0

### SECTION 1 Identification

#### 1.1. Product identifier

Product form : Mixture  
Product name : ProActive

#### 1.2. Other means of identification

No additional information available

#### 1.3. Recommended use of the chemical and restrictions on use

Recommended use : Fuel additives  
Restrictions on use : Use only in liquid fuel systems

#### 1.4. Supplier's details

##### Manufacturer

Fuel Right  
41 Germay Drive  
Wilmington, DE, 19804  
USA  
T 302-425-4400  
[info@fuelright.com](mailto:info@fuelright.com)

#### 1.5. Emergency phone number

Emergency number : CHEMTREC (800) 424-9300

### SECTION 2 Hazard identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Flammable liquids, Category 4  
Skin irritation, Category 2  
Serious eye damage, Category 1

#### 2.2. Label elements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Combustible liquid  
Causes skin irritation  
Causes serious eye damage

Precautionary statements (GHS) :

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Wash hands, forearms and face thoroughly after handling.  
Wear protective gloves, protective clothing, eye protection, face protection.  
If on skin: Wash with plenty of water.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation occurs: Get medical advice or attention.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

and easy to do. Continue rinsing.

Immediately call a poison center or doctor.

In case of fire: Use dry extinguishing powder, alcohol resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish.

Store in a well-ventilated place.

Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and international regulation.

### 2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

### 2.4. Hazards not otherwise classified

No additional information available

### 2.5. Unknown acute toxicity

Not applicable

## SECTION 3 Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)Weight
Dipropylene glycol monomethyl ether	Dipropylene glycol monomethyl ether Dipropylene glycol monomethyl ether / (2-Methoxymethylethoxy)propanol / Propanol, (2-methoxymethylethoxy)- / Dipropylene glycol methyl ether / DPGME / PPG-2 METHYL ETHER / Methoxypropoxypropanol / (2-Methoxymethylethoxy)propanol, mixed isomers / Monomethyl ether of dipropyleneglycol / 1(or 2)-[2-Methoxy(methyl)ethoxy]propanol / PPG-2 methyl ether / (2-Methoxymethylethoxy) propanol	CAS-No.: 34590-94-8	30 - 60*
Cyclic Amino Compound*	-	Trade Secret*	10 -30*

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)Weight
Petroleum distillates, hydrotreated light	Petroleum distillates, hydrotreated light Hydrotreated light distillate / Kerosene, hydrotreated / Petroleum distillates, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 150-290°C.) / Odorless light petroleum hydrocarbons / Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, / Kerosene / c13-14 isoparaffin / Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9-14 Aliphaten) / Light Aliphatic Hydrocarbon / Odourless light petroleum hydrocarbons / Distillates (petroleum), hydro- treated light; Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).] / Distillates, petroleum, hydrotreated light / Distillates (petroleum), hydrotreated light	CAS-No.: 64742-47-8	7 - 13*
Aliphatic Diamine*	-	Trade Secret*	3 - 7*

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

## SECTION 4 First-aid measures

### 4.1. Description of necessary first-aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

### 4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Dry extinguishing powder, alcohol resistant foam, carbon dioxide (CO <sub>2</sub> ).
Unsuitable extinguishing media	: Do not use water jet.

### 5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid. Products of combustion may include, and are not limited to: oxides of carbon. Oxides of nitrogen.
-------------	---

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

## SECTION 6 Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges.
------------------	---

#### For non-emergency personnel

No additional information available

#### For emergency responders

Environmental precautions	: Prevent entry to sewers and public waters.
---------------------------	--

### 6.2. Methods and materials for containment and cleaning up

For containment	: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Spilled material may present a slipping hazard. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 7 Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Keep away from sources of ignition - No smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection.
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.

#### 7.2. Conditions for safe storage, including incompatibilities

Storage conditions	: Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Keep cool.
--------------------	--

### SECTION 8 Exposure controls/personal protection

#### 8.1. Control parameters

<b>ProActive</b>	
No additional information available	
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
No additional information available	
<b>Dipropylene glycol monomethyl ether (34590-94-8)</b>	
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Dipropylene glycol methyl ether (DPGME)
ACGIH® TLV® TWA	50 ppm (Dipropylene glycol methyl ether)
Remark (ACGIH)	TLV® Basis: Liver & CNS eff
Regulatory reference	ACGIH 2024
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Dipropylene glycol methyl ether
OSHA PEL TWA	600 mg/m <sup>3</sup>
OSHA PEL TWA	100 ppm
Limit value category (OSHA)	prevent or reduce skin absorption
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	600 ppm
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	600 mg/m <sup>3</sup>
NIOSH REL TWA	100 ppm
NIOSH REL STEL	900 mg/m <sup>3</sup>
NIOSH REL STEL	150 ppm
US-NIOSH chemical category	Potential for dermal absorption

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### Aliphatic Diamine (Trade Secret)

No additional information available

### Cyclic Amino Compound (Trade Secret)

No additional information available

## 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.  
Environmental exposure controls : Avoid release to the environment.

## 8.3. Individual protection measures, such as personal protective equipment

### Hand protection:

Wear suitable gloves resistant to chemical penetration. Nitrile rubber gloves. Butyl rubber gloves

### Eye protection:

Wear eye protection. tightly fitting safety goggles. Safety glasses with side shields

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9 Physical and chemical properties

### 9.1. Basic physical and chemical properties

Physical state : Liquid  
Colour : Amber Pale yellow  
Odour : No data available  
Odour threshold : No data available  
pH : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : No data available  
Flash point : 85 °C (185 °F) closed cup  
Flammability (solid, gas) : Combustible liquid.  
Upper flammability or explosive concentration limit : No data available  
Lower flammability or explosive concentration limit : No data available  
Vapour pressure : No data available  
Relative vapour density at 20°C/ 68 °F : No data available  
Relative density : No data available  
Solubility : No data available  
Partition coefficient n-octanol/water : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity, kinematic : 34 mm<sup>2</sup>/s  
Explosive limits : No data available  
Particle characteristics : No data available

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Petroleum distillates, hydrotreated light	
Boiling point	146 – 299 °C Atm. press.: 101,325 kPa
Flash point	29 – 70 °C Atm. press.: 101,325 kPa
Auto-ignition temperature	> 200 °C (at 1013 hPa)
Vapour pressure	0.01 – 0.3 hPa (at 20 °C)
Particle characteristics	No data available

Dipropylene glycol monomethyl ether	
Boiling point	189.6 °C (at 760 mmHg)
Flash point	75 °C (closed cup)
Auto-ignition temperature	270 °C
Particle characteristics	No data available

### 9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

## SECTION 10 Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Heat. Sources of ignition. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Oxides of nitrogen. May release flammable gases.

## SECTION 11 Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg (Source: IUCLID)

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
LD50 dermal rabbit	> 2000 mg/kg (Source: NLM_CIP)
LC50 inhalation rat	> 5.2 mg/l/4h
<b>Dipropylene glycol monomethyl ether (34590-94-8)</b>	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rat	> 19020 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	9510 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
<b>Dipropylene glycol monomethyl ether (34590-94-8)</b>	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: other:KANPOGYO No.700, YAKUHATSU No. 1039.61, and KIKYKU No. 1014.
NOAEL (dermal, rat/rabbit, 90 days)	2850 mg/kg bodyweight Animal: rabbit, Animal sex: male, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
Aspiration hazard	: Not classified.
<b>ProActive</b>	
Viscosity, kinematic	34 mm <sup>2</sup> /s
<b>Petroleum distillates, hydrotreated light (64742-47-8)</b>	
Viscosity, kinematic	No data available
<b>Dipropylene glycol monomethyl ether (34590-94-8)</b>	
Viscosity, kinematic	No data available
<b>Aliphatic Diamine (Trade Secret)</b>	
Viscosity, kinematic	No data available

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Cyclic Amino Compound (Trade Secret)	
Viscosity, kinematic	No data available
Expected Symptoms/Effects, Acute and Delayed	: Causes serious eye damage. Causes skin irritation.
Likely routes of exposure	: Ingestion. Inhalation. Oral. Dermal.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

## SECTION 12 Ecological information

### 12.1. Ecotoxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 - Fish [1]	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: IUCLID)
LC50 - Fish [2]	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)

Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 - Other aquatic organisms [1]	1930 mg/l Test organisms (species): other aquatic crustacea:Acartia tonsa
EC50 72h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 969 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'
NOEC (chronic)	≥ 0.5 mg/l Test organisms (species): Daphnia magna Duration: '22 d'

### 12.2. Persistence and degradability

ProActive	
Persistence and degradability	Not established.

Petroleum distillates, hydrotreated light (64742-47-8)	
Persistence and degradability	Rapidly degradable

Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable

Aliphatic Diamine (Trade Secret)	
Persistence and degradability	Rapidly degradable

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Cyclic Amino Compound (Trade Secret)	
Persistence and degradability	Rapidly degradable

### 12.3. Bioaccumulative potential

ProActive	
Bioaccumulative potential	Not established.

Petroleum distillates, hydrotreated light (64742-47-8)	
BCF - Fish [1]	61 – 159

Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water	0.35 (at 25 °C (at pH 7)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Ozone	: Not classified.
Fluorinated greenhouse gases	: No
Other information	: No other effects known.

## SECTION 13 Disposal considerations

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information	: Handle empty containers with care because residual vapours are flammable.

## SECTION 14 Transport information

In accordance with DOT / TDG

### 14.1. UN Number

UN-No. (DOT)	: NA1993
UN-No. (TDG)	: Not regulated

### 14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Combustible liquid, n.o.s. (Dipropylene glycol monomethyl ether)
Proper Shipping Name (TDG)	: Not regulated

### 14.3. Transport hazard class(es)

<b>DOT</b> Transport hazard class(es) (DOT)	: Combustible liquid
--	----------------------

<b>TDG</b> Transport hazard class(es) (TDG)	: Not regulated
--	-----------------

### 14.4. Packing group

Packing group (DOT)	: III
Packing group (TDG)	: Not regulated

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Transport in bulk

Not applicable

### 14.7. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

#### DOT

Not Regulated in Non-Bulk Containers

UN-No. (DOT) : NA1993

DOT Special Provisions (49 CFR 172.102) : 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)).  
IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### TDG

Not regulated

## SECTION 15 Regulatory information

### 15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

# ProActive

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

### SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 2025-08-21  
Issue date : 2020-03-17  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



Indication of changes:			
SDS update.			
Section	Changed item	Comments	Version
SDS	Physical and chemical properties. GHS classification. Transport information.	Modified	2.0
SDS	SDS update	Modified	3.0

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.